# Power PRO series
## X2600

16 MP | 26X Zoom | 3" LCD | HD Video

Available Colors:

## More power, More full

Some things just keep getting better, like the new X2600 from GE. Mega zoom and mega features meet extreme value in our best-selling bridge camera line. 16 megapixels, 26X optical zoom with a wide-angle lens and HD video are just the beginning. Put the newest GE Power PRO camera to the test and start shooting like a pro.

imagination at work

# Camera Features

# X2600

### pancapture
Wide-view photos are produced by panning the camera across to create a seamless panoramic picture.

### face detection
Recognizes the faces in the scene to focus on the true subject of your shot.

### 720p HD video
Captures all of your videos in high definition 720p resolution.

### HDMI
Connect the camera via HDMI cable to share your high-resolution videos instantly.

### ISO 1600
Improves pictures in low lighting condition for optimal exposure.

### optical image stabization
Automatically adjusts for unintentional camera movements, giving you clear, crisp pictures every time.

### wide angle lens
A wider angle lens allows you to capture a larger scene or group shot than a traditional lens.

### AA battery
Convenient, easy and no hassle AA batteries keep you on the go.

| SPECIFICATIONS* | X2600 |
|---|---|
| Number Of Active Pixels | 16.08 Megapixels |
| Image Sensor | 16.44 Megapixels [1/2.3" Charge Coupled Device (CCD)] |
| Lens Focal Length F = | 4.7 mm (Wide) – 122.2 mm (Tele) |
| [ 35mm film equivalent ] | [ 26 mm (Wide) – 676 mm (Tele) |
| F number | f / 3.2 (Wide) – f / 5.6 (Tele) |
| Lens Construction | 14 elements in 10 groups |
| Optical Zoom | 26X |
| Focusing Range | Normal: (Wide) 19.7 in. – ∞ / 50 cm – ∞, (Tele) 86.6 in – ∞ / 220 cm – ∞<br>Macro: (Wide) 3.9 in. – 23.6 in. / 10 cm – 60 cm, (Tele) 86.6 in. – 118.1 in. / 220 cm – 300 cm<br>Super Macro: 0.4 in. – 5.9 in. / 1 cm – 15 cm (Wide only) |
| Anti-Handshake | Optical Image Stabilization |
| Digital Zoom | 5 x Digital Zoom (Combined Zoom: 130x) |
| Number of Recording Pixels | |
| Still Image | 16MP: 4608×3456, (3:2) 14MP: 4608×3072, (6:9) 12MP: 4608×2592, 6MP: 2880×2160, 3MP: 2048×1536 |
| Movie | 1280×720 (30fps), 640×480 (30fps) |
| DCF, DPOF (Ver1.1) Support | Yes |
| File Format | |
| Still Image | Exif 2.3 (JPEG) |
| Movie | Movie Format: H.264 (MP4), Audio: AAC [Monaural] |
| Shooting Modes | Auto Scene, P, M, Sport, Night Landscape, Landscape, Panorama, Night Portrait, Portrait, Scene [Children, Sunset, Backlight, Self Portrait, High ISO, Photo booth, Bright, Candle light, Stage, Fireworks, Flower], Movie |
| Detection Features | Face Detection, Face Recognition, Red-eye Removal |
| LCD Display | 3.0 inch (230,000 pixels) |
| Panorama Capture Still Image | Yes (Horizontal) [3 Shots] |
| ISO Sensitivity | Auto, 64 / 100 / 200 / 400 / 800 / 1600 |
| AF Method | Continuous AF, Single AF |
| Exposure Metering Method | Multi-Pattern, Center-Weighted, Face Priority |
| Exposure Control Method | Program AE (AE-lock available) |
| Exposure Compensation | ± 2.0 EV With 1/3 EV Steps |
| Shutter Speed | |
| Smart Capture Mode | Auto (1/2–1/2000 sec.) |
| M Mode | 16 – 1/1000 sec. |
| Playback Modes | Still Capture: Single-up, Multi-up (Thumbnails), Magnify, Slideshow<br>Video Capture: FF/Rewind, Pause, By Frame, Volume Control, Multi-up (Thumbnail), Slideshow |
| White Balance Control | Auto, Daylight, Tungsten, Fluorescent, Open Shade |
| Flash | Pop-up |
| Flash Modes | Auto (With Digital Red-eye Reduction), Auto + Red-eye Reduction (With Pre-Flash and Digital Red-eye Reduction), Fill (With Digital Red-eye Reduction), OFF |
| Shooting Range | (Wide) 19.7 – 216.5 in. / 50 – 550 cm at ISO 400, Smart Capture<br>(Tele) 86.6 – 122.1 in. / 220 – 310 cm at ISO 800, Smart Capture |
| Recording Media | Internal Memory: Approx. 28MB<br>SDHC/SD Support (32GB) |
| Other Features | PictBridge, ExifPrint Support, Multi-Language Support (21 Languages) |
| Jacks | AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D) |
| Power | 4AA Battery |
| Shooting Capability (Battery Performance) | Approx. 300 shots for AA Alkaline Batteries (based on CIPA Standards) |
| Operation Environment | Temperature: 32° – 104° / 0 – 40°, Humidity: 0 – 90% |
| Dimensions (W x H x D) | Approx. 4.6 × 3.1 × 2.9 in. / 116.4 × 78.8 × 73 mm |
| Mass | 488g with In-box Battery (Alkaline) |
| Supplied Accessories | 4AA Alkaline Battery, USB Cable, Lens Cover, Shoulder Strap, Manual, Warranty Card |

*Design and specifications are subject to change without notice.
For complete specifications and detailed product information, please visit www.ge.com/digitalcameras.

V 12.12.14